

THE TTR EUROWORKS 4U PRODUCT RANGE WORKS FOR YOU!

# WR4U 200

## PREMIUM WAX/RESIN

This Premium Wax/Resin is highly versatile and delivers exceptional print quality and abrasion resistance on a broad range of substrates, including rough and smooth surfaces.

WAX

WAX-RESIN

RESIN

W-R NEAR EDGE

R NEAR EDGE

WR4U 200

## PRODUCT SUMMARY

- ✓ Low print energy and antistatic formulation for easy handling and printhead protection
- ✓ Extensive label adaptability for wax & wax/resin applications
- ✓ Superior abrasion resistance
- ✓ Delivers excellent blackness & high definition
- ✓ Prints well on rough and/or porous surfaces

## TECHNICAL SPECIFICATIONS

PET film thickness	4,5 microns
Total ribbon thickness	6,7 microns
Transmissional density	≥ 1,0 MacBeth Scale
Ink melting point	70 °C / 158 °F
Print-speed up to	250 mm / second
Recommended media	(Un)coated tag, label stock, glossy papers, P.E and P.P. labels

## CHARACTERISTICS

Scrath resistance	✓✓✓✓↓
Smudge resistance	✓✓✓✓✓
Sensitivity	✓✓✓✓○
Rotated barcode sharpness	✓✓✓↓○
Fine line printability	✓✓✓✓○

## APPLICATIONS



## COMPLIANCE

- ✓ TSCA
- ✓ REACH - SVHC Free
- ✓ RoHS/WEEE
- ✓ ISEGA
- ✓ Additional regulatory requirements upon request