

THE TTR EUROWORKS 4U PRODUCT RANGE WORKS FOR YOU!

W4U 100

ECONOMIC WAX

Unbeatable economical printing without making concessions to quality and printing performances.

WAX	WAX-RESIN	RESIN	W-R NEAR-EDGE	R NEAR-EDGE
W4U 100		W4U 110		W4U 120

PRODUCT SUMMARY

- ✓ Low print energy and anti-static formulation for easy handling and print head protection
- ✓ Outstanding print quality & durable image
- ✓ High blackness & fine definition
- ✓ Applicable to various types of labels and tags
- ✓ Coating technology for print head protection

TECHNICAL SPECIFICATIONS

PET film thickness	4,5 microns
Total ribbon thickness	6,8 microns
Transmissional density	≥ 1,1 MacBeth Scale
Ink melting point	67 °C / 152 °F
Recommended max. print-speed	280 mm / second
Recommended media	(Un)coated tag, label stock and glossy papers

CHARACTERISTICS

Scratch resistance	✓ ✓ ✓ ○ ○
Smudge resistance	✓ ✓ ✓ ○ ○
Sensitivity	✓ ✓ ✓ ✓ ✓
Rotated barcode sharpness	✓ ✓ ✓ ✓ ○
Fine line printability	✓ ✓ ✓ ○ ○

APPLICATIONS



COMPLIANCE

- ✓ TSCA
- ✓ REACH – SVHC Free
- ✓ RoHS/WEEE
- ✓ ISEGA
- ✓ Additional regulatory requirements upon request