THE TTR EUROWORKS 4U PRODUCT RANGE WORKS FOR YOU!

WR4U 210 **ECONOMIC WAX/RESIN**

This unbeatable very economical Wax/Resin makes no concessions to quality, abrasion resistance and other printing performances on a versatile range of substrates, including rough and smooth surfaces.

WAX-RESIN **WR4U 210**

PRODUCT SUMMARY

- Extensive label adaptability for wax & wax/resin applications
- Superior abrasion resistance
- Low print energy and antistatic formulation for easy handling and printhead protection
- ✓ Delivers excellent blackness & high definition
- ✓ Prints well on rough and/or porous surfaces

TECHNICAL SPECIFICATIONS

PET film thickness	4,5 microns
Total ribbon thickness	7,0 microns
Transmissional density	≥ 1,8 MacBeth Scale
Ink melting point	67 °C / 152,6 °F
Print-speed up to	300 mm / second
Recommended media	(Un)coated tag, label stock, glossy papers, P.E and P.P. labels

CHARACTERISTICS

Scrath resistance	00000
Smudge resistance	0000
Sensitivity	0000
Rotated barcode sharpness	00000
Fine line printability	00000

APPLICATIONS





Shipping Shelf & Bin Nursery





Retail





Tags

COMPLIANCE

TSCA

REACH - SVHC Free

RoHS/WEEE



Additional regulatory requirements upon request

